



# FALCON Equipment Specifications



## Standard Equipment

20'

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
19'4"	7'8"	7'10"	7'8"	7'6"	4,916 lbs	66,579 lbs	1,172 ft <sup>3</sup>
5.900 m	2.352 m	2.340 m	2.342 m	2.292 m	2,230 kgs	30,200 kgs	33.2 m <sup>3</sup>

40'

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
39'5"	7'8"	7'10"	7'8"	7'6"	8,267 lbs	63,383 lbs	2,391 ft <sup>3</sup>
12.029 m	2.352 m	2.340 m	2.342 m	2.292 m	3,750 kgs	28,750 kgs	67.7 m <sup>3</sup>

40' High Cube

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
39'5"	7'8"	8'10"	7'8"	8'6"	8,708 lbs	63,603 lbs	2,695 ft <sup>3</sup>
12.029 m	2.352 m	2.700 m	2.342 m	2.597 m	3,950 kgs	28,550 kgs	76.3 m <sup>3</sup>

45' High Cube

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
44'5"	7'8"	8'10"	7'8"	8'6"	10,362 lbs	61,288 lbs	3,037 ft <sup>3</sup>
13.556 m	2.352 m	2.700 m	2.342 m	2.597 m	4,700 kgs	27,800 kgs	86.0 m <sup>3</sup>

# Special Equipment

## 20' Open Top

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
19'4"	7'7"	7'8"	7'6"	7'2"	5,402 lbs	66,248 lbs	1,148 ft <sup>3</sup>
5.900 m	2.311 m	2.354 m	2.286 m	2.814 m	2,450 kgs	30,050 kgs	32.5 m <sup>3</sup>

## 40' Open Top

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
39'5"	7'8"	7'8"	7'8"	7'5"	8,488 lbs	58,708 lbs	2,345 ft <sup>3</sup>
12.028 m	2.350 m	2.315 m	2.341 m	2.274 m	3,850 kgs	26,630 kgs	66.4 m <sup>3</sup>

## 20' Flat Rack

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
18'5"	7'3"	7'4"	-	-	5,578 lbs	47,332 lbs	-
5.864 m	2.311 m	2.354 m	-	-	2,530 kgs	21,470 kgs	-

## 40' Flat Rack

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
39'7"	6'10"	6'5"	-	-	12,081 lbs	85,800 lbs	-
12.028 m	2.350 m	2.315 m	-	-	5,480 kgs	39,000 kgs	-

## 20' Refrigerated

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
17'8"	7'5"	7'5"	7'5"	7'3"	7,040 lbs	45,760 lbs	1,000 ft <sup>3</sup>
5.452 m	2.275 m	2.260 m	2.258 m	2.216 m	3,200 kgs	20,800 kgs	28.3 m <sup>3</sup>

## 40' Refrigerated

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
37'8"	7'5"	7'2"	7'8"	7'0"	10,780 lbs	56,276 lbs	2,040 ft <sup>3</sup>
11.493 m	2.270 m	2.197 m	2.282 m	2.155 m	4,900 kgs	25,580 kgs	57.8 m <sup>3</sup>

## 40' High Cube Refrigerated

Interior Length	Interior Width	Interior Height	Door Width	Door Height	Tare Weight	Max Payload Weight	Capacity
37'11"	7'6"	8'2"	7'6"	8'0"	9,900 lbs	57,561 lbs	2,344 ft <sup>3</sup>
11.557 m	2.294 m	2.500 m	2.294 m	2.440 m	4,500 kgs	25980 kgs	66.6 m <sup>3</sup>

The above specifications are approximations to be used as a basic reference. Actual container dimensions vary within container series.

Max payload weights do not take max legal weight road restrictions into consideration.

Please email a Falcon representative for any additional information.